



## PN16 Brass Y Strainer

### Features

- Screwed BSP Parallel
- Stainless Steel Mesh
- Brass Body

DN	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
ø	8	10	15	20	25	32	40	50	65	80	90
F	10	10	11	13	15	15	17	18	19	20	25
S	46	46	55	68	75	96	105	125	146	170	210
H	33	33	40	48	50	68	70	90	105	125	155
Kgs	0.01	0.01	0.13	0.21	0.31	0.64	0.79	1.44	2.00	3.20	6.40
Mesh	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	1.5	1.5	1.5
L	2	2	2	2	2	2	2	2	3	3	3
L1	1	1	1	1	1	1	1	1	1.5	1.5	1.5
flow cm <sup>2</sup>	34	34	34	34	34	34	34	34	21	21	21

N.	Part Name	Materials
1	Body	Brass CW617N - UNI EN 12165/98
2	Filter	Stainless Steel AISI304
3	Gasket	PTFE
4	Plug	Brass CW617N - UNI EN 12165/98

Technical Data	
Max Pressure	16 bar
Working Temperature	-10°C to +90°C

