

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 14/02/2025 Revision date: 02/09/2024 Supersedes version of: 28/09/2022 Version: 1.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : INDUSTRIAL DEGREASER FG
UFI : 84MY-F8JM-Y005-VTPM

Product code : BDS000272AE
Type of product : Detergent
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Cleaners - Heavy duty

1.3. Details of the supplier of the safety data sheet

Supplier Only Representative

CRC Industries Europe UK Limited

CRC Industries Europe B.V.

Wylds Road

Touwslagerstraat 1

Castlefield Industrial Estate 9240 Zele
TA6 4DD Bridgwater Somerset Belgium

United Kingdom T +32(0)52/45.60.11, F +32(0)52/45.00.34 T +44 1278 727200, F +44 1278 425644 hse@crcind.com, www.crcind.com

T +44 1278 727200, F +44 1278 425644 hse.uk@crcind.com, www.crcind.com

nse.uk@crcina.com, www.crcina.com

1.4. Emergency telephone number

Emergency number : +44 1278 727200

Office hours: 9-17h CET

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229 Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Aspiration hazard, Category 1 H304

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Signal word (CLP) : Danger

Contains : Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics;2-methoxy-1-

methylethyl acetate;1-methoxy-2-propanol; monopropylene glycol methyl ether;butan-2-ol

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated. H336 - May cause drowsiness or dizziness.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258- 33	50 – 75	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336
1-methoxy-2-propanol; monopropylene glycol methyl ether substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435- 35	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336
Carbon dioxide (CO2) (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 124-38-9	1 – 5	Press. Gas (Comp.), H280
butan-2-ol substance with national workplace exposure limit(s) (BE)	CAS-No.: 78-92-2 EC-No.: 201-158-5 EC Index-No.: 603-127-00-5 REACH-no: 01-2119475146- 36	≤5	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H336 STOT SE 3, H335

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory

symptoms: Call a poison center or a doctor. Allow the victim to rest. If signs/symptoms

develop, get medical attention.

First-aid measures after skin contact : Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Wash

skin with plenty of water. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or

redness persists. Seek medical attention if irritation develops.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Avoid the spillage or runoff entering drains, sewers or watercourses.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Clean

contaminated surfaces with an excess of water. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual

contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety

procedures.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Carbon dioxide (CO2) (124-38-9)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Carbon dioxide	
IOEL TWA	9000 mg/m³	
	5000 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
Belgium - Occupational Exposure Limits		
Local name	Carbone (dioxyde de) # Koolstofdioxide	
OEL TWA	9131 mg/m³	
	5000 ppm	
OEL STEL	54784 mg/m³	
	30000 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carbon dioxide (CO2) (124-38-9)	
Remark	A: la mention "A" signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # A: de vermelding "A" betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m³
	50 ppm
IOEL STEL	550 mg/m³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Acétate de 2-(1-méthoxy)propyle # 2-(1-Methoxy)propylacetaat
OEL TWA	275 mg/m³
	50 ppm
OEL STEL	550 mg/m³
	100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
1-methoxy-2-propanol; monopropylene glyco	l methyl ether (107-98-2)
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	1-Methoxypropanol-2
IOEL TWA	375 mg/m³
	100 ppm
IOEL STEL	568 mg/m³
	150 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	1-Méthoxy-2-propanol # 1-Methoxy-2-propanol
OEL TWA	184 mg/m³

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
	50 ppm
OEL STEL	369 mg/m³
	100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
butan-2-ol (78-92-2)	
Belgium - Occupational Exposure Limits	
Local name	Alcool sec-butylique # sec-Butanol
OEL TWA	307 mg/m³
	100 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

DNEL and PNEC

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics DNEL/DMEL (Workers) Long-term - systemic effects, dermal 208 mg/kg bodyweight/day Long-term - systemic effects, inhalation 871 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 125 mg/kg bodyweight/day Long-term - systemic effects, inhalation 185 mg/m³ Long-term - systemic effects, inhalation 185 mg/m³ Long-term - systemic effects, dermal 125 mg/kg bodyweight/day 2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 38 mg/kg bodyweight/day Long-term - systemic effects, inhalation 37 mg/m³ Long-term - local effects, inhalation 37 mg/m³ Long-term - local effects, inhalation 37 mg/m³ Long-term - local effects, inhalation 37 mg/m³ PNEC (Water) PNEC (Water) PNEC (aqua (freshwater) 0,635 mg/l PNEC aqua (intermittent, freshwater) 0,0635 mg/l	DNEL and PNEC	DNEL and PNEC	
Long-term - systemic effects, inhalation 871 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, inhalation 125 mg/kg bodyweight/day Long-term - systemic effects, inhalation 125 mg/kg bodyweight/day Long-term - systemic effects, inhalation 125 mg/kg bodyweight/day 2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, inhalation 33 mg/m³ PNEC (Water) PNEC (Water) PNEC (Quar (freshwater)) 0,635 mg/l PNEC aqua ((marine water)) 0,0635 mg/l	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral 125 mg/kg bodyweight/day Long-term - systemic effects, inhalation 125 mg/kg bodyweight/day 2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day DNEL/DMEL (General population) Acute - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0.635 mg/l PNEC aqua (marine water) 0.0635 mg/l	DNEL/DMEL (Workers)		
DNEL/DMEL (General population) Long-term - systemic effects, oral 185 mg/m³ Long-term - systemic effects, inhalation 185 mg/m³ 2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, inhalation 33 mg/m³ PNEC (Water) PNEC (Water) PNEC aqua (freshwater) 0.635 mg/l PNEC aqua (marine water) 0.0635 mg/l	Long-term - systemic effects, dermal	208 mg/kg bodyweight/day	
Long-term - systemic effects, oral Long-term - systemic effects, inhalation 185 mg/m³ 2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day 2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 200 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - systemic effects, inhalation	871 mg/m³	
Long-term - systemic effects, inhalation 185 mg/m³ 2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, inhalation 320 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	DNEL/DMEL (General population)		
Long-term - systemic effects, dermal 2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral Long-term - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, inhalation 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 37 mg/kg bodyweight/day Long-term - systemic effects, inhalation 38 mg/kg bodyweight/day Long-term - systemic effects, inhalation 39 mg/kg bodyweight/day Long-term - local effects, inhalation 30 mg/kg bodyweight/day Long-term - local effects, inhalation 30 mg/kg bodyweight/day Long-term - local effects, inhalation 30 mg/kg bodyweight/day DNEC aqua (freshwater) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water)	Long-term - systemic effects,oral	125 mg/kg bodyweight/day	
2-methoxy-1-methylethyl acetate (108-65-6) DNEL/DMEL (Workers) Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, inhalation 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - systemic effects, inhalation	185 mg/m³	
Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - systemic effects, dermal	125 mg/kg bodyweight/day	
Acute - local effects, inhalation 550 mg/m³ Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	2-methoxy-1-methylethyl acetate (108-65-6)		
Long-term - systemic effects, dermal 796 mg/kg bodyweight/day Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	DNEL/DMEL (Workers)		
Long-term - systemic effects, inhalation 275 mg/m³ DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Acute - local effects, inhalation	550 mg/m³	
DNEL/DMEL (General population) Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - systemic effects, dermal	796 mg/kg bodyweight/day	
Acute - systemic effects, oral 500 mg/kg bodyweight/day Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - systemic effects, inhalation	275 mg/m³	
Long-term - systemic effects, oral 36 mg/kg bodyweight/day Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	DNEL/DMEL (General population)		
Long-term - systemic effects, inhalation 33 mg/m³ Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Acute - systemic effects, oral	500 mg/kg bodyweight/day	
Long-term - systemic effects, dermal 320 mg/kg bodyweight/day Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - systemic effects,oral	36 mg/kg bodyweight/day	
Long-term - local effects, inhalation 33 mg/m³ PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - systemic effects, inhalation	33 mg/m³	
PNEC (Water) PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - systemic effects, dermal	320 mg/kg bodyweight/day	
PNEC aqua (freshwater) 0,635 mg/l PNEC aqua (marine water) 0,0635 mg/l	Long-term - local effects, inhalation	33 mg/m³	
PNEC aqua (marine water) 0,0635 mg/l	PNEC (Water)		
· · · · · · · · · · · · · · · · · · ·	PNEC aqua (freshwater)	0,635 mg/l	
PNEC aqua (intermittent, freshwater) 6,35 mg/l	PNEC aqua (marine water)	0,0635 mg/l	
	PNEC aqua (intermittent, freshwater)	6,35 mg/l	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-methoxy-1-methylethyl acetate (108-65-6)		
PNEC (Sediment)		
PNEC sediment (freshwater)	3,29 mg/kg dwt	
PNEC sediment (marine water)	0,329 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,29 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
1-methoxy-2-propanol; monopropylene glyco	l methyl ether (107-98-2)	
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	553,5 mg/m³	
Acute - local effects, inhalation	553,5 mg/m³	
Long-term - systemic effects, dermal	183 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	369 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	33 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	43,9 mg/m³	
Long-term - systemic effects, dermal	78 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	10 mg/l	
PNEC aqua (marine water)	1 mg/l	
PNEC aqua (intermittent, freshwater)	100 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	52,3 mg/kg dwt	
PNEC sediment (marine water)	5,2 mg/kg dwt	
PNEC (Soil)		
PNEC soil	4,59 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
butan-2-ol (78-92-2)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	405 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	600 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	15 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	213 mg/m³	
Long-term - systemic effects, dermal	203 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	47,1 mg/l	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butan-2-ol (78-92-2)		
PNEC aqua (marine water)	47,1 mg/l	
PNEC aqua (intermittent, freshwater)	47,1 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	196,19 mg/kg dwt	
PNEC sediment (marine water)	196,19 mg/kg dwt	
PNEC (Soil)		
PNEC soil	11,58 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	1000 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	761 mg/l	

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):





Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Colourless.

Appearance : CO2 propelled liquid.
Odour : Slightly ethereal.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : 100 – 200 °C

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Lower explosion limit Not available Upper explosion limit Not available : 23 °C (closed cup) Flash point : > 200 °C Auto-ignition temperature Decomposition temperature : Not available рΗ : Not applicable Viscosity, kinematic $< 20.5 \text{ mm}^2/\text{s}$ Solubility : Insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not applicable Vapour pressure : Not available Vapour pressure at 50°C : Not available : 0,81 g/cm3 at 20 °C Density Relative density : 0,81 at 20 °C Relative vapour density at 20°C : Not available

9.2. Other information

Particle characteristics

Information with regard to physical hazard classes

% of flammable ingredients : 75 – 100 %

Other safety characteristics

VOC content : 783 a/l

Additional information : For aerosols data for the product without propellant.

: Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 11: Toxicological information

2-methoxy-1-methylethyl acetate (108-65-6)

11.1 Information on hazard classes as defined in Regulation (FC) No.	1272/2000

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (illinatation)	. Not classified (based off available data, the classification chieffa are not met)
Hydrocarbons, C9-C11, n-alkanes, is	oalkanes, cyclics, < 2% aromatics
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
2-methoxy-1-methylethyl acetate (10	8-65-6)
LD50 oral rat	> 5000 mg/kg
LD50 oral	8532 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LD50 dermal	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 10800 mg/l
1-methoxy-2-propanol; monopropyle	ene glycol methyl ether (107-98-2)
LD50 oral rat	4016 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 25,8 mg/l
butan-2-ol (78-92-2)	
LD50 oral rat	2193 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Serious eye damage/irritation	 Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)

Hydrocarbone C9_C11 n-alkanes isoalkanes cyclics < 2% aromatics	
STOT-single exposure	: May cause drowsiness or dizziness.
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure	May cause drowsiness or dizziness.	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
STOT-single exposure	May cause drowsiness or dizziness.	
2-methoxy-1-methylethyl acetate (108-65-6)		
STOT-single exposure	May cause drowsiness or dizziness.	
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
STOT-single exposure	May cause drowsiness or dizziness.	
butan-2-ol (78-92-2)		
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.	
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met)	

= moundary i mounty control (100 00 0)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight	
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight	
Aspiration hazard : May be fatal if swallowed and enters airways.		
INDUSTRIAL DEGREASER FG		
Vaporizer	Aerosol	
Viscosity, kinematic	< 20,5 mm²/s	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Viscosity, kinematic	1,33 mm²/s	

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

Viscosity, kinematic 1,848 mm²/s

butan-2-ol (78-92-2)

Viscosity, kinematic 5,185 mm²/s

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term : Not classified (Based on available data, the classification criteria are not met) (chronic)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
LC50 - Fish [1]	> 1000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l
EC50 - Other aquatic organisms [1]	> 1000 mg/l
EC50 72h - Algae [1]	> 1000 mg/l
2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 500 mg/l
EC50 - Other aquatic organisms [1]	408 mg/l
EC50 - Other aquatic organisms [2]	> 1000 mg/l
EC50 72h - Algae [1]	> 1000 mg/l
NOEC (chronic)	≥ 100 mg/l

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-methoxy-1-methylethyl acetate (108-65-6)		
NOEC chronic fish	47,5 mg/l	
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
LC50 - Fish [1]	6812 mg/l	
LC50 - Fish [2]	20800 mg/l	
EC50 - Crustacea [1]	21100 – 25900 mg/l	
EC50 - Other aquatic organisms [1]	2954 mg/l	
ErC50 algae	> 1000 mg/l	
butan-2-ol (78-92-2)		
LC50 - Fish [1]	2993 mg/l	
EC50 - Crustacea [1]	308 mg/l	
EC50 72h - Algae [1]	1972 mg/l	
EC50 96h - Algae [1]	2029 mg/l	

12.2. Persistence and degradability

INDUSTRIAL DEGREASER FG	
Persistence and degradability	Not established. No data is available on the degradability of this product.

12.3. Bioaccumulative potential

INDUSTRIAL DEGREASER FG		
Partition coefficient n-octanol/water (Log Kow)	Not applicable	
Carbon dioxide (CO2) (124-38-9)		
Partition coefficient n-octanol/water (Log Pow)	0,83	
2-methoxy-1-methylethyl acetate (108-65-6)		
Partition coefficient n-octanol/water (Log Pow)	1,2	
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
Bioconcentration factor (BCF REACH)	< 100	
Partition coefficient n-octanol/water (Log Pow)	0,37	
butan-2-ol (78-92-2)		
Partition coefficient n-octanol/water (Log Pow)	0,65	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

INDUSTRIAL DEGREASER FG	
Results of PBT assessment	Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

INDUSTRIAL DEGREASER FG	
Other information	No other effects known
Global warming potential (GWP)	0,05 (Fluorinated greenhouse gases - (EC) No 2024/573)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

European List of Waste (LoW, EC 2000/532)

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
4.1. UN number or ID n	umber			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
ransport document descri	iption			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2
14.3. Transport hazard c	class(es)			
2.1	2.1	2.1	2.1	2.1
2	2	2	2	2
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information	n available			

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN): 1 LExcepted quantities (ADN): E0Equipment required (ADN): PP, EX, AVentilation (ADN): VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L
Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

02/09/2024 (Revision date) BE - en 14/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 783 g/l

Detergent Regulation (648/2004)

Labelling of contents	
Component	%
aliphatic hydrocarbons	≥30%

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Comp.)	Gases under pressure : Compressed gas
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.