

SAFETY DATA SHEET

PLUS GAS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PLUS GAS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier Saint Gobain Abrasives
Doxey Road
Stafford
England
ST16 1EA
01785 222000
www.saint-gobain.co.uk

1.4. Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229
Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xi;R38. F+;R12. N;R51/53. R67.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H315 Causes skin irritation.
H229 Pressurised container: may burst if heated
H411 Toxic to aquatic life with long lasting effects.
H222 Extremely flammable aerosol.
H336 May cause drowsiness or dizziness.

PLUS GAS

Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective clothing, gloves, eye and face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P302+P352 IF ON SKIN: Wash with plenty of water. P332+P313 If skin irritation occurs: Get medical advice/attention. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/container in accordance with national regulations.
---------------------------------	---

Contains Kerosine (Petroleum), Hydrodesulfurized

Detergent labelling ≥ 30% aliphatic hydrocarbons

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Kerosine (Petroleum), Hydrodesulfurized		60-100%
CAS number: 64742-81-0	EC number: 265-184-9	REACH registration number: 01-2119462828-25-xxxx
Classification Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R38. N;R51/53. R67.	
White Mineral Oil (Petroleum)		5-10%
CAS number: 8042-47-5	EC number: 232-455-8	REACH registration number: 01-2119487078-27-XXXX
Classification Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention immediately.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

PLUS GAS

Eye contact Rinse with water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation May cause drowsiness or dizziness.

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation.

Eye contact May cause discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Extremely flammable aerosol. Pressurised container: may burst if heated

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Provide adequate ventilation. Avoid inhalation of vapours and contact with skin and eyes. If ventilation is inadequate, suitable respiratory protection must be worn. Take care as floors and other surfaces may become slippery. Avoid contact with contaminated tools and objects. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. Provide adequate ventilation. Wipe up with an absorbent cloth and dispose of waste safely. Absorb spillage with inert, damp, non-combustible material. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

PLUS GAS

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves. Avoid contact with skin and eyes. Do not breathe vapour/spray. Do not expose to temperatures exceeding 50°C/122°F. Provide adequate ventilation. Keep container in a well-ventilated place. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Do not empty into drains. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store at temperatures between 4°C and 40°C. Do not expose to temperatures exceeding 50°C/122°F.

Storage class

Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

KEROSINE (PETROLEUM), HYDRODESULFURIZED

Long-term exposure limit (8-hour TWA): OES 300 mg/m³

KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS: 64742-81-0)

DNEL

- Oral; Long term : 19 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Rubber (natural, latex). Neoprene. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

PLUS GAS

Hygiene measures Wash hands thoroughly after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Clear.
Odour	Mild. Solvent.
pH	Not applicable.
Solubility(ies)	Insoluble in water.

9.2. Other information

Other information	Not determined.
-------------------	-----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not determined.
------------------------------------	-----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Flammable/combustible materials.
--------------------	----------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂).
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Aspiration hazard

Aspiration hazard	Aspiration hazard if swallowed.
-------------------	---------------------------------

Inhalation	May cause drowsiness or dizziness.
------------	------------------------------------

Ingestion	May cause discomfort. Aspiration hazard if swallowed.
-----------	---

Skin contact	Causes skin irritation.
--------------	-------------------------

Eye contact	May cause discomfort.
-------------	-----------------------

Toxicological information on ingredients.

KEROSINE (PETROLEUM), HYDRODESULFURIZED

Acute toxicity - oral

PLUS GAS

Acute toxicity oral (LD₅₀ 5,000.0
mg/kg)

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.1
mg/kg)

Species Rabbit

ATE dermal (mg/kg) 2,000.1

Acute toxicity - inhalation

Acute toxicity inhalation 5.29
(LC₅₀ dust/mist mg/l)

Species Rat

ATE inhalation 5.29
(dusts/mists mg/l)

WHITE MINERAL OIL (PETROLEUM)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 2,000.1
mg/kg)

Species Rat

ATE oral (mg/kg) 2,000.1

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.1
mg/kg)

Species Rat

ATE dermal (mg/kg) 2,000.1

Acute toxicity - inhalation

Acute toxicity inhalation 2,000.1
(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours 2,000.1
mg/l)

SECTION 12: Ecological Information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Acute toxicity - fish Not determined.

Ecological information on ingredients.

PLUS GAS

KEROSINE (PETROLEUM), HYDRODESULFURIZED

Acute toxicity - fish	LC ₅₀ , 96 hours: 2 - 5 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 1.4 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 1 - 3 mg/l, Algae
Chronic toxicity - fish early life stage	, 28 days, 28 days: .098 mg/l, Onchorhynchus mykiss (Rainbow trout)
Chronic toxicity - aquatic invertebrates	, 21 days, 21 days: 0.89 , Daphnia magna

WHITE MINERAL OIL (PETROLEUM)

Acute toxicity - fish	LC ₅₀ , 96 hours, 96 hours: > 400,000 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 96 hours, 96 hours: > 500,000 mg/l, Marinewater invertebrates EC ₅₀ , 48 hours: 500000 ppm mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface.

Ecological information on ingredients.

WHITE MINERAL OIL (PETROLEUM)

Mobility The product is immiscible with water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

KEROSINE (PETROLEUM), HYDRODESULFURIZED

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

PLUS GAS

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

PLUS GAS

EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ATE: Acute Toxicity Estimate. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level. IATA: International Air Transport Association. IMDG: International Maritime Dangerous Goods. PBT: Persistent, Bioaccumulative and Toxic substance. PNEC: Predicted No Effect Concentration. vPvB: Very Persistent and Very Bioaccumulative.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	29/02/2016
Revision	2.1
Supersedes date	04/02/2015
Risk phrases in full	R12 Extremely flammable. R38 Irritating to skin. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.