

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: CASSIDA GREASE GTS SPRAY

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricating grease

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS (UK) PLC.
New Century Street
ST1 5HU Hanley
Telephone: +44 (0) 1782 203700

Contact Person: Product Safety department
E-mail: product.safety@fuchs.com
Telephone: +44 (0) 1782 203700

1.4 Emergency telephone number: UK NHS: Dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation GB-CLP.

Classification according to GB-CLP.

Physical Hazards

Aerosol	Category 1	H222: Extremely flammable aerosol. H229: Pressurized container: May burst if heated.
---------	------------	---

Environmental Hazards

Chronic hazards to the aquatic environment	Category 3	H412: Harmful to aquatic life with long lasting effects.
--	------------	--

Hazard summary

Physical Hazards: No data available.

2.2 Label Elements

Product name: CASSIDA GREASE GTS SPRAY**Signal Words:** Danger**Hazard Statement(s):**
H222: Extremely flammable aerosol.
H229: Pressurized container: May burst if heated.
H412: Harmful to aquatic life with long lasting effects.**Precautionary Statements****General information:** P102: Keep out of reach of children.**Prevention:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P273: Avoid release to the environment.**Storage:** P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.**Disposal:** P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Supplemental label information**

EUH208: Contains: Calcium Sulfonate. May produce an allergic reaction.

2.3 Other hazards: The product may not be released into the environment without control.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****General information:** Mixture of components with propellant in aerosol can.

Product name: CASSIDA GREASE GTS SPRAY

Chemical name	Identifier	Concentration *	UK-REACH Registration No.	Notes
Propane	EINECS: 200-827-9	0% - <75,00%		
Butane (<0,1% 1,3-butadiene)	EINECS: 203-448-7	0% - <75,00%		
Isobutane (<0,1% 1,3-butadiene)	EINECS: 200-857-2	0% - <75,00%		
Hydrocarbons, low viscous	EC: 923-037-2	10,00% - <20,00%		
Calcium Sulfonate	EINECS: 263-093-9	1,00% - <5,00%		
Calcium Sulfonate	EINECS: 271-529-4	1,00% - <5,00%		
Ca Sulfonate	EINECS: 274-263-7	1,00% - <5,00%		
Amine aromatic , alkylated	EINECS: 270-128-1	0,10% - <1,00%		

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification	
Propane	EINECS: 200-827-9	GBCLP:	Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280
Butane (<0,1% 1,3-butadiene)	EINECS: 203-448-7	GBCLP:	Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280
Isobutane (<0,1% 1,3-butadiene)	EINECS: 200-857-2	GBCLP:	Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280
Hydrocarbons, low viscous	EC: 923-037-2	GBCLP:	Flam. Liq. 3;H226, Asp. Tox. 1;H304, Aquatic Chronic 2;H411 EUH066
Calcium Sulfonate	EINECS: 263-093-9	GBCLP:	Skin Sens. 1B;H317
Calcium Sulfonate	EINECS: 271-529-4	GBCLP:	Skin Sens. 1B;H317
Ca Sulfonate	EINECS: 274-263-7	GBCLP:	Skin Sens. 1B;H317
Amine aromatic , alkylated	EINECS: 270-128-1	GBCLP:	Repr. 2;H361f

GB-CLP

specific concentration limit

Chemical name	Identifier	specific concentration limit	Hazard class	Hazard Category	Hazard statements
Calcium Sulfonate	EINECS: 263-093-9	>= 10 %	Skin sensitizer	1B	H317
Calcium Sulfonate	EINECS: 271-529-4	>= 10 %	Skin sensitizer	1B	H317
Ca Sulfonate	EINECS: 274-263-7	>= 10 %	Skin sensitizer	1B	H317

For the wording of the listed hazard statements refer to section 16.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Product name: CASSIDA GREASE GTS SPRAY

Skin Contact:	Wash with soap and water.
Ingestion:	Rinse mouth thoroughly.
4.2 Most important symptoms and effects, both acute and delayed:	May cause skin and eye irritation.
4.3 Indication of any immediate medical attention and special treatment needed	Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture:

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire-fighting procedures: Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from sources of ignition - No smoking.

6.2 Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up:

Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to regulations.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

Product name: CASSIDA GREASE GTS SPRAY

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Provide adequate ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products.

7.2 Conditions for safe storage, including any incompatibilities: Local regulations concerning handling and storage of waterpolluting products have to be followed.

7.3 Specific end use(s): Not applicable

Storage Class: 2 B, Aerosols

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Butane (<0,1% 1,3-butadiene)	TWA	600 ppm 1.450 mg/m ³	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
Butane (<0,1% 1,3-butadiene)	STEL	750 ppm 1.810 mg/m ³	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)

8.2 Exposure controls

Appropriate engineering controls: Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eye/face protection: Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield. Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

Product name: CASSIDA GREASE GTS SPRAY**Skin protection****Hand Protection:**

Material: Nitrile butyl rubber (NBR).

Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Do not breathe dust/fume/gas/mist/vapors/spray. Provide adequate ventilation. In case of inadequate ventilation wear respiratory protection. Filter AX/P2. Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

Thermal hazards:

Not known.

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls:

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state:	Aerosol
Form:	Aerosol
Color:	Beige
Odor:	Odorless
pH:	substance/mixture is non-soluble (in water)
Freezing point:	not determined
Boiling Point:	not determined
Flash Point:	< -60 °C (DIN EN ISO 2719)
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	not determined
Explosion Limit - Upper (%):	Not applicable for mixtures
Explosion Limit - Lower (%):	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	0,95 g/cm3 (15 °C) (DIN 51757)
Solubility(ies)	
Solubility in Water:	The product is insoluble in water.
Solubility (other):	No data available.

Product name: CASSIDA GREASE GTS SPRAY

Partition coefficient (n-octanol/water):	Not applicable for mixtures
Auto-ignition temperature:	not determined
Decomposition Temperature:	not determined
NLGI:	2
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
Particle characteristics:	Not applicable
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	No data available.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Oral**

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

Hydrocarbons, low viscous LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Calcium Sulfonate LD 50 (Rat): > 16.000 mg/kg

Calcium Sulfonate LD 50 (Rat): > 5.001 mg/kg

Ca Sulfonate LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Product name: CASSIDA GREASE GTS SPRAY**Dermal**

Product:	Not classified for acute toxicity based on available data.
Specified substance(s)	
Hydrocarbons, low viscous	LD 50 (Rabbit): > 5.000 mg/kg (OECD 402)
Calcium Sulfonate	LD 50 (Rat): > 5.001 mg/kg
Calcium Sulfonate	LD 50 (Rabbit): > 5.001 mg/kg
Ca Sulfonate	LD 50 (Rabbit): > 5.000 mg/kg (OECD 402)

Inhalation

Product:	Not classified for acute toxicity based on available data.
Specified substance(s)	
Butane (<0,1% 1,3-butadiene)	LC 50 (Rat, 4 h): 658 mg/l Gas
Hydrocarbons, low viscous	LC 50 (Rat, 4 h): > 5,6 mg/l

Skin Corrosion/Irritation:

Product:	Based on available data, the classification criteria are not met.
Specified substance(s)	
Calcium Sulfonate	OECD 404 (Rabbit): Not irritant.
Calcium Sulfonate	OECD 404 (Rabbit): Not irritant.
Ca Sulfonate	OECD 404 (Rabbit): Not irritant.

Serious Eye Damage/Eye Irritation:

Product:	Based on available data, the classification criteria are not met.
Specified substance(s)	
Calcium Sulfonate	OECD 405 (Rabbit): Not irritant.

Respiratory or Skin Sensitization:

Product:	Skin sensitizer: Based on available data, the classification criteria are not met. Respiratory sensitizer: Based on available data, the classification criteria are not met.
Specified substance(s)	
Calcium Sulfonate	May cause sensitization by skin contact.
Calcium Sulfonate	May cause sensitization by skin contact.
Ca Sulfonate	May cause sensitization by skin contact.

Product name: CASSIDA GREASE GTS SPRAY

Germ Cell Mutagenicity

Product:

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration Hazard

Product:

Based on available data, the classification criteria are not met.

Other adverse effects:

No data available.

SECTION 12: Ecological information

General information: Not applicable Not applicable

12.1 Toxicity

Acute toxicity

Product:

Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Propane

LC 50 (Fish, 96 h): > 1.000 mg/l

Isobutane (<0,1% 1,3-butadiene)

LC 50 (Fish, 96 h): 28 mg/l

Hydrocarbons, low viscous

LC 50 (Fish, 96 h): > 1.000 mg/l (OECD 203)

Calcium Sulfonate

LC 50 (Fish, 96 h): > 10.000 mg/l (OECD 203)

Calcium Sulfonate

LL 50 (Cyprinodon variegatus, 96 h): > 10.000 mg/l (OECD 203)

Ca Sulfonate

LC 50 (Fish, 96 h): > 1.001 mg/l (OECD 203)

Aquatic Invertebrates

Specified substance(s)

Isobutane (<0,1% 1,3-butadiene)

EC 50 (Water Flea, 48 h): 16,3 mg/l

Hydrocarbons, low viscous

LC 50 (Water Flea, 48 h): > 1.000 mg/l (OECD 202)

Calcium Sulfonate

EC 50 (Water Flea, 48 h): > 100 mg/l (OECD 202)

Product name: CASSIDA GREASE GTS SPRAY

Calcium Sulfonate EL50 (Daphnia magna, 48 h): > 1.000 mg/l

Ca Sulfonate EC 50 (Water Flea, 48 h): > 1.001 mg/l

Chronic Toxicity

Product: Based on available data, the classification criteria are met.

Fish**Specified substance(s)**

Hydrocarbons, low viscous NOEC (Fish, 28 d): 0,192 mg/l

Aquatic Invertebrates**Specified substance(s)**

Hydrocarbons, low viscous NOEC (Water Flea, 21 d): < 1 mg/l (OECD 211)

Toxicity to Aquatic Plants**Specified substance(s)**

Isobutane (<0,1% 1,3-butadiene) EC 50 (Alga, 72 h): 8,6 mg/l

Hydrocarbons, low viscous EC 50 (Alga, 72 h): > 1.000 mg/l (OECD 201)
NOEC (Alga, 72 h): > 1.000 mg/l (OECD 201)

Calcium Sulfonate EL50 (Algae (Pseudokirchneriella subcapitata), 96 h): > 1.000 mg/l

Ca Sulfonate EC 50 (Alga, 72 h): > 1.000 mg/l

12.2 Persistence and Degradability**Biodegradation****Product:**

Not applicable for mixtures

Specified substance(s)

Hydrocarbons, low viscous 31,3 % (28 d, OECD 301E) Inherently biodegradable

Calcium Sulfonate 8,6 % (28 d) Not easily biodegradable

12.3 Bioaccumulative potential**Product:**

Not applicable for mixtures

12.4 Mobility in soil:**Product:**

Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

Harmful to aquatic life with long lasting effects.

Water Hazard Class (WGK):

WGK 1: slightly water-endangering.

Product name: CASSIDA GREASE GTS SPRAY

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local laws.

List of Waste (LoW) Codes

16 05 04*: Gases in pressure containers (including halons) containing hazardous substances.

SECTION 14: Transport information**ADR/RID**

14.1 UN number or ID number:	UN 1950
14.2 UN Proper Shipping Name:	AEROSOLS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
Hazard No. (ADR):	—
Tunnel restriction code:	(D)
14.4 Packing Group:	—
14.5 Environmental hazards:	—
14.6 Special precautions for user:	—

IMDG

14.1 UN number or ID number:	UN 1950
14.2 UN Proper Shipping Name:	AEROSOLS
14.3 Transport Hazard Class(es)	
Class:	2.1
Label(s):	2.1
EmS No.:	F-D, S-U
14.3 Packing Group:	—
14.5 Environmental hazards:	—
14.6 Special precautions for user:	—

IATA

14.1 UN number or ID number:	UN 1950
14.2 Proper Shipping Name:	Aerosols, flammable
14.3 Transport Hazard Class(es)	
Class:	2.1
Label(s):	2.1
14.4 Packing Group:	—
14.5 Environmental hazards:	—
14.6 Special precautions for user:	—

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

Product name: CASSIDA GREASE GTS SPRAY

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

GB Regulations

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019:

none

The Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020:

none

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

DIRECTIVE Control of Major Accident Hazards Regulations 2015:

Hazard category in accordance with GB-CLP	Qualifying quantity for the application of Lower-tier requirements:	Qualifying quantity for the application of Upper-tier requirements:
P3a: P3a. Flammable aerosols	150 t	500 t

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapor.
H229	Pressurized container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Other information:

The classification complies with the current GB lists; however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: On the basis of test data; Calculation Method; Bridging Principle "Substantially similar mixtures"; Expert Judgement

Revision Date:

24.03.2025

Product name: CASSIDA GREASE GTS SPRAY**Disclaimer:**

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.

Abbreviations and acronyms:

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EIGA - European Industrial Gases Association; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative