# **PORTWEST**.

**PRODUCT SPECIFICATION & TECHNICAL DATA** 

## **PW40 - Classic Ear Protector**

Collection: Ear Muffs Range: Hearing Protection Materials: ABS, Polycarbonate, PVC Inner Pack: 10 Outer Carton: 60

#### **Product information**

Lightweight and robust, the  $\ensuremath{\text{PW40}}$  is suitable for all day comfort. Excellent attenuation rate.

#### Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colours for earmuffs allow a personalised choice. An updated range of earplugs complete our competitive and performing offer.

#### **Hearing Protection**

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

### Standards

EN 352-1 (SNR 28dB) ANSI S3.19 (NRR 22dB) AS/NZS 1270 (SLC(80) 28dB - Class 5)



### Features

- Ultra light and compact ear muff
- Adjustable length for a secure and comfortable fit
- 100% metal free
- CE certified
- CE-CAT III
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines

# **PORTWEST**<sub>®</sub>

**PRODUCT SPECIFICATION & TECHNICAL DATA** 

# PW40 - Classic Ear Protector Commodity Code: 6506101000

**Test House** Cert No: Q3930A

Cert No: CE 698123 I

#### **CARTON DIMENSIONS/WEIGHT**

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m <sup>3</sup> )	EAN13	DUN14
PW40RER	Red	62.0	44.0	51.0	0.1600	0.1391	5036108134656	15036108636201

# **PERFORMANCES - SOUND ATTENUATION - EN 352-1:2002**

<b>PW40/PS40 SNR 27.6dB H:</b> 29.2 <b>M:</b> 25.4 <b>L:</b> 17.9									
A Frequency (Hz)		63	125	250	500	1000	2000	4000	8000
В	Mean Attenuation (dB)	18.1	15.0	18.3	26.8	37.5	29.5	35.8	36.1
C	Standard Deviation (dB)	4.1	2.7	3.3	2.0	4.1	2.9	3.3	5.8
D	Assumed Protection (dB)	14.0	12.3	15.0	24.8	33.4	26.6	32.5	30.3

PW40RER