

Safety Data Sheet according to Regulation (EC) No1907/2006

Page 1 of 11

SDS No.: 168433

V003.5

Revision: 30.01.2014

printing date: 04.02.2014

Loctite 542

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite 542

Contains:

Cumene hydroperoxide

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Anaerobic Sealant

1.3. Details of the supplier of the safety data sheet

Henkel Limited

2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 +44 1606 863762 Fax-no.:

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation. Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment Category 3

H412 Harmful to aquatic life with long lasting effects.

MSDS-No.: 168433 Loctite 542 Page 2 of 11

V003.5

Classification (DPD):

Xn - Harmful

R20 Harmful by inhalation.

Xi - Irritant

R36/37 Irritating to eyes and respiratory system.

Dangerous for the environment

 $R52/53 \ Harmful\ to\ aquatic\ organisms,\ may\ cause\ long-term\ adverse\ effects\ in\ the\ aquatic\ environment.$

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word: Warning

Hazard statement: H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement: ***For consumer use only: P101 If medical advice is needed, have product container or

label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in

accordance with local authority requirements***

Precautionary statement: P261 Avoid breathing vapours.

Prevention P273 Avoid release to the environment.

Precautionary statement: P337+P313 If eye irritation persists: Get medical advice/attention.

Response

MSDS-No.: 168433 Loctite 542 Page 3 of 11

V003.5

Label elements (DPD):

Xn - Harmful



Risk phrases:

R20 Harmful by inhalation.

R36/37 Irritating to eyes and respiratory system.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S23 Do not breathe vapour.

S25 Avoid contact with eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S51 Use only in well-ventilated areas.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

Contains:

Cumene hydroperoxide, N,N-dimethyl-o-toluidine

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

General chemical description:

Anaerobic Sealant

MSDS-No.: 168433 Loctite 542 Page 4 of 11

V003.5

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Cumene hydroperoxide 80-15-9	201-254-7	>= 2,5-< 3 %	Organic peroxides E H242 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Dermal H312 Acute toxicity 4; Oral H302 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 2 H411 Skin corrosion 1B H314
N,N-dimethyl-o-toluidine 609-72-3	210-199-8	> 0,1-< 0,9 %	Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Acute toxicity 3; Oral H301 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 3 H412
1,4-Naphthalenedione 130-15-4	204-977-6	>= 0,01-< 0,1 %	Acute toxicity 3; Oral H301 Skin irritation 2; Dermal H315 Skin sensitizer 1; Dermal H317 Serious eye irritation 2 H319 Acute toxicity 1; Inhalation H330 Specific target organ toxicity - single exposure 3; Inhalation H335 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410 M factor: 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Cumene hydroperoxide	201-254-7	>= 2,5 -< 3 %	T - Toxic; R23
80-15-9			Xn - Harmful; R21/22, R48/20/22
			C - Corrosive; R34
			O - Oxidizing; R7
			N - Dangerous for the environment; R51/53
Cumene	202-704-5	> 0,1 - < 1 %	R10
98-82-8			Xn - Harmful; R65
			Xi - Irritant; R37
			N - Dangerous for the environment; R51/53
N,N-dimethyl-o-toluidine	210-199-8	> 0,1 -< 0,9 %	T - Toxic; R23/24/25
609-72-3			R33
			R52/53
1,4-Naphthalenedione	204-977-6	>= 0,01 -< 0,1 %	T+ - Very toxic; R25, R26
130-15-4			Xi - Irritant; R36/37/38, R43
			N - Dangerous for the environment; R50/53

MSDS-No.: 168433 Loctite 542 Page 5 of 11

V003.5

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eve contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

In case of fire, keep containers cool with water spray.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

Ensure adequate ventilation.

See advice in section 8

6.2. Environmental precautions

Do not let product enter drains.

MSDS-No.: 168433 Loctite 542 Page 6 of 11

V003.5

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Hygiene measures

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

7.3. Specific end use(s)

Anaerobic Sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient	ppm	mg/m ³	Type	Category	Remarks
CUMENE	50	250	Short Term Exposure		EH40 WEL
98-82-8			Limit (STEL):		
CUMENE			Skin designation:	Can be absorbed through the	EH40 WEL
98-82-8				skin.	
CUMENE	25	125	Time Weighted Average		EH40 WEL
98-82-8			(TWA):		
CUMENE	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
CUMENE	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA):		

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

MSDS-No.: 168433 Loctite 542 Page 7 of 11

V003.5

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid brown
Odor characteristic

Odour threshold No data available / Not applicable

pH 3-6

()

Initial boiling point Not determined Flash point $> 100 \, ^{\circ}\text{C} \ (> 212 \, ^{\circ}\text{F})$

Decomposition temperature No data available / Not applicable

Vapour pressure 0,1 mm hg
Density 1,08 g/cm3

()

Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Not miscible (Solvent: Water)

Solubility (qualitative) Slight

Solidification temperature

Melting point

No data available / Not applicable

No data available / Not applicable

Flammability

No data available / Not applicable

Auto-ignition temperature

No data available / Not applicable

Explosive limits

No data available / Not applicable

Partition coefficient: n-octanol/water

No data available / Not applicable

Evaporation rate Not available. Vapor density Not available.

Oxidising properties No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids. Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

MSDS-No.: 168433 Loctite 542 Page 8 of 11

V003.5

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

Irritating organic vapours. Oxides of carbon. Sulphur oxides nitrogen oxides

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

May cause respiratory irritation.

Skin irritation:

Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Causes serious eye irritation.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral	time	rat	

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

MSDS-No.: 168433 Loctite 542 Page 9 of 11

V003.5

SECTION 12: Ecological information

General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards.

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Harmful to aquatic life with long lasting effects.

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
			Study			
Cumene hydroperoxide	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
80-15-9						203 (Fish, Acute
						Toxicity Test)
Cumene hydroperoxide	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
80-15-9			_			202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Cumene hydroperoxide	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
80-15-9						201 (Alga, Growth
						Inhibition Test)
1,4-Naphthalenedione	EC50	0,011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline
130-15-4						201 (Alga, Growth
						Inhibition Test)

12.2. Persistence and degradability

Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
Cumene hydroperoxide		no data	0 %	OECD Guideline 301 B (Ready
80-15-9				Biodegradability: CO2 Evolution
				Test)
1,4-Naphthalenedione		no data	0 - 60 %	
130-15-4				

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Bioaccumulative potential:

No data available.

Hazardous components	LogKow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Cumene hydroperoxide		9,1		calculation		OECD Guideline 305
80-15-9						(Bioconcentration: Flow-
						through Fish Test)
Cumene hydroperoxide	2,16					-
80-15-9						
1,4-Naphthalenedione	1,71					
130-15-4						

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

MSDS-No.: 168433 Loctite 542 Page 10 of 11

V003.5

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.4. Packaging group

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 5 % (1999/13/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 168433 Loctite 542 Page 11 of 11

V003.5

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.

R21/22 Harmful in contact with skin and if swallowed.

R23 Toxic by inhalation.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R25 Toxic if swallowed.

R26 Very toxic by inhalation.

R33 Danger of cumulative effects.

R34 Causes burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R37 Irritating to respiratory system.

R43 May cause sensitisation by skin contact.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.